

3300X Legendary Reliability

Avoids Hand Contact With Push Paddle Taps

- Manual taps and lack of any PCB's or solenoids makes for easy maintenance
- Built on the same platform, and uses many of the same parts as the well known, ArcticChill88/98 and ArcticStar55
- The 3300X fits our overflow kit, our cowlings and mains drainage kit with or without pump



Push The Glass Or Cup
Against The Tap To
Dispense



Robust & Reliable
The Epitome
Of Perseverance

Quality – Reliability – Integrity

3300X Legendary Reliability

Avoids Hand Contact With Push Paddle Taps

Accessories For The 3300X

Installation rail with filter.
Includes compression fitting,
1-Micron green filter,
water block, copper pressure
reducing valve & non-return
valve




Filter housing with carbon
block candle & nanofilter



Cowling to fix the cooler
securely to the wall.
(Supplied separately)



Mains drainage - connect
the drip tray to mains
drainage. Can be supplied
with a pump, to pump the
water over 50m & a rise
of 5m



10 litre overflow system
with alarm to signal when
full. (Factory fitted)



A pumped main drainage
system pumps the waste
water from the drip tray
over a distance of 100m & a
rise of 5m.
(Factory installed)



3 Litre overflow kit
connects the drip tray
to a 3 litre alarmed
overflow container. The
container has a tap to
empty without
removing it



Description	Dimensions H x W x D mm	Weight
POU floor standing	1135 x 340 x 340	18
Bottled floor standing	1165 x 340 x 340	18
POU table top	460 x 340 x 340	15
Bottled table top	463 x 340 x 340	15