ArcticChill 88

Exceptional Capacity Direct Chill

- Direct chill cold water cooler
- Single dispensing button for chilled water
- Can be fitted with overflow kits & mains drainage
- Fits our standard cowling and wall bracket
- WRAS approved
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height

Delivers 30 - 40 Litres Per Hour Of Chilled Water Below 12˚C



23cm Dispensing Height To Fill Bottles

Description	Dimensions H X W X D (MM)	Weight (Kg)
POU Floor Standing	1135 x 340 x 340	25
POU Table Top	460 x 340 x 340	16

WRAS APPROVED PRODUCT

Quality – Reliability – Integrity

ArcticChill 88

Exceptional Capacity Direct Chill





Accessories For The ArcticChill 88

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve




FloodGuard - closed inlet solenoid only opens to allow water into the cooler, when water is dispensed. By remaining closed all other times it protects the cooler against leaks



Filter housing with carbon block candle & nanofilter



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m




Cowling to fix the cooler securely to the wall. (Supplied separately)



10 litre overflow system with alarm to signal when full. (Factory fitted)



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)

